

PREISE - PRICES

ABMESSUNGEN mm DIMENSIONS mm	FILTEROBER- FLÄCHE m² FILTER SURFACE m²	Luftdurchsatz m³/h AIR FLOW m³/h	ΔP (Pa) NTE6	ΔP (Pa) NTE7	ΔP (Pa) NTE9	NTE6	NTE7	NTE9
						€	€	€
287x592x292	7	2.100	110	130	150			
490x592x292	11	3.500	110	130	150			
592x592x292	14	4.250	100	130	150			

Betriebsdaten - Working data	
Zusammensetzung Filterelement - Filter medium composition	Mikroglasfaser - Glass micro fibre
Material Rahmen - Frame material	Kunststoff - Plastic
Maximale Betriebstemperatur - Max working temperature	65 °C
Betrieb bei relativer Luftfeuchtigkeit, max. - Max working R.H.	90%
Farbmetrische Effizienz - Colorimetric efficiency	NTE6=65% NTE7=85% NTE9=95%
Klassifizierung (EN 779:2002) - Classification (EN 779:2002)	NTE6=F6 NTE7=F7 NTE9=F8/9
Regenerationsfähigkeit - Regeneration	NEIN



MERKMALE:

Filter mit steifen Taschen
F6 - F7 - F8/9.

CHARACTERISTICS:

Rigid bag filters
F6 - F7 - F8/9.

