



MERKMALE:

Schlauch aus Netzpolyester mit einem Auftrag von einem speziellen PVC, verstärkt mit Federstahlschicht, die zwischen zwei thermogeschweißten Schichten eingebettet ist. Der Luftkontaktbereich wurde antibakteriell behandelt.

Antibakterielle Behandlung: Sanitized®

Bogenradius

0,6 x Ø

Standardlängen:

10 m

Betriebstemperaturen:

von 10 °C bis +80 °C

ANWENDUNGEN:

Luftverteilung in Krankenhäusern. Luftverteilung in Reinräumen.

CHARACTERISTICS:

Flexible duct made of mesh fabric coated polyester with special PVC, reinforced with spiral steel wire embedded between two layers of thermowelded, with antibacterial treatment of the area of contact with the air.

Antibacterial treatment Sanitized®

Bending radius:

0.6 x diameter

Lengths:

10 m

Working temperature:

10 °C to 80 °C

APPLICATIONS:

Air distribution in a hospital setting. Air distribution in cleanrooms.

PREISE - PRICES

	€
82	
102	
127	
152	
160	
203	
254	
305	
315	
356	
406	
508	

Hinweis: Preise per Meter
Notes: prices per meter

KLASSIFIZIERUNG DER BRANDREAKTION REACTION TO FIRE CLASSIFICATION

EN 13823: 2020

EN ISO 11925: 2020

EN 13501-1: 2019

B - s2, d0