

## PRECIOS - PRICES

| DIMENSIONES mm<br>DIMENSIONS mm | SUPERFICIE<br>FILTRANTE m <sup>2</sup><br>FILTER<br>SURFACE m <sup>2</sup> | CAUDAL DE<br>AIRE m <sup>3</sup> /h<br>AIR FLOW<br>m <sup>3</sup> /h | ΔP (Pa)<br>NTE6 | ΔP (Pa)<br>NTE7 | ΔP (Pa)<br>NTE9 | NTE6 | NTE7 | NTE9 |
|---------------------------------|----------------------------------------------------------------------------|----------------------------------------------------------------------|-----------------|-----------------|-----------------|------|------|------|
|                                 |                                                                            |                                                                      |                 |                 |                 | €    | €    | €    |
| 287x592x292                     | 7                                                                          | 2.100                                                                | 110             | 130             | 150             |      |      |      |
| 490x592x292                     | 11                                                                         | 3.500                                                                | 110             | 130             | 150             |      |      |      |
| 592x592x292                     | 14                                                                         | 4.250                                                                | 100             | 130             | 150             |      |      |      |

### Datos de funcionamiento - Working data

|                                                             |                                          |
|-------------------------------------------------------------|------------------------------------------|
| Composición media filtrante - Filter medium composition     | Microfibra de vidrio - Glass micro fibre |
| Material bastidor - Frame material                          | Plástico - Plastic                       |
| Temperatura máx de funcionamiento - Max working temperature | 65 °C                                    |
| H.R. máx de funcionamiento - Max working R.H.               | 90%                                      |
| Eficiencia colorimétrica - Colorimetric efficiency          | NTE6=65% NTE7=85% NTE9=95%               |
| Clasificación (EN 779:2002) - Classification (EN 779:2002)  | NTE6=F6 NTE7=F7 NTE9=F8/9                |
| Regenerabilidad - Regeneration                              | NO                                       |



### CARACTERÍSTICAS:

Filtros de bolsas rígidas  
F6 - F7 - F8/9.

### CHARACTERISTICS:

Rigid bag filters  
F6 - F7 - F8/9.

