

**CARACTERÍSTICAS:**

Plénium de chapa para bocas de impulsión y de retorno con: acople trasero (PBZ1) acople lateral (PBZ2) para la conexión al tubo flexible.

VERSIÓN:

No aislado (PBZ)
Aislamiento externo (PBZI)

CHARACTERISTICS:

Galvanized steel plenum for supply and return grilles. Available with rear (PBZ1) and side (PBZ2) spigot for mounting of flexible duct.



VERSIONS:

Not insulated (PBZ)
External insulated (PBZI)

PBZ1 - PBZI1

DIMENSIONES - DIMENSIONS		Ø D	N.º acoples N. spigots
B x H	L		
200x100	200	100	1
300x100	200	100	1
400x100	200	100	2
500x100	200	100	2
600x100	200	100	2
700x100	200	100	2
800x100	200	100	2
900x100	200	100	3
1000x100	200	100	3
1200x100	200	100	3
200x150	200	150	1
300x150	200	150	1
400x150	200	150	1
500x150	200	150	2
600x150	200	150	2
700x150	200	150	2
800x150	200	150	2
900x150	200	150	2
1000x150	200	150	3
1200x150	200	150	3
200x200	200	200	1
300x200	200	200	1
400x200	200	200	1
500x200	200	200	1
600x200	200	200	2
700x200	200	200	2
800x200	200	200	2
900x200	200	200	2
1000x200	200	200	2
1200x200	200	200	2
300x300	200	250	1
400x300	200	250	1
500x300	200	250	1

DIMENSIONES - DIMENSIONS		Ø D	N.º acoples N. spigots
B x H	L		
600x300	200	200	2
700x300	200	200	2
800x300	200	250	2
900x300	200	250	2
1000x300	200	250	2
1200x300	200	250	2
400x400	200	300	1
500x400	200	300	1
600x400	200	200	2
700x400	200	300	2
800x400	200	300	2
900x400	200	300	2
1000x400	200	300	2
1200x400	200	300	2
500x500	200	350	1
600x500	200	350	1
700x500	200	350	1
800x500	200	350	2
900x500	200	350	2
1000x500	200	350	2
1200x500	200	350	2
600x600	200	350	1
700x600	200	350	1
800x600	200	350	2
900x600	200	350	2
1000x600	200	350	2
1200x600	200	350	2
800x800	200	350	2
900x800	200	350	2
1000x800	200	350	2
1200x800	200	400	2
560x560	200	350	1

DIBUJOS - DRAWINGS**PBZI1**

Plénium aislado externamente espesor 6 mm
Plenum externally insulated thickness 6 mm


PBZ2 - PBZI2

DIMENSIONES - DIMENSIONS		Ø D	N.º acoples N. spigots
B x H	L		
200x100	220	100	1
300x100	220	100	1
400x100	220	100	1
500x100	220	100	1
600x100	220	100	1
700x100	220	100	1
800x100	220	100	1
900x100	220	100	1
1000x100	220	100	1
1200x100	220	100	1
200x150	270	150	1
300x150	270	150	1
400x150	270	150	1
500x150	270	150	1
600x150	270	150	1
700x150	270	150	1
800x150	270	150	1
900x150	270	150	1
1000x150	270	150	1
1200x150	270	150	1
200x200	320	200	1
300x200	320	200	1
400x200	320	200	1
500x200	320	200	1
600x200	320	200	1
700x200	320	200	1
800x200	320	200	1
900x200	320	200	1
1000x200	320	200	1
1200x200	320	200	1
300x300	370	250	1
400x300	370	250	1
500x300	370	250	1


DIMENSIONES - DIMENSIONS		Ø D	N.º acoples N. spigots
B x H	L		
600x300	370	250	1
700x300	370	250	1
800x300	370	250	1
900x300	370	250	1
1000x300	370	250	1
1200x300	370	250	1
400x400	420	300	1
500x400	420	300	1
600x400	420	300	1
700x400	420	300	1
800x400	420	300	1
900x400	420	300	1
1000x400	420	300	1
1200x400	420	300	1
500x500	470	350	1
600x500	470	350	1
700x500	470	350	1
800x500	470	350	1
900x500	470	350	1
1000x500	470	350	2
1200x500	470	350	2
600x600	470	350	1
700x600	470	350	1
800x600	470	350	1
900x600	470	350	2
1000x600	470	350	2
1200x600	470	350	2
800x800	470	350	2
900x800	470	350	2
1000x800	470	350	2
1200x800	520	400	2
560x560	470	350	1

DIBUJOS - DRAWINGS

PBZ2



PBZI2



Plénium aislado externamente espesor 6 mm
Plenum externally insulated thickness 6 mm