


PHD20



CARACTERÍSTICAS:

Panel sandwich espesor 20,5 mm.
Aluminio: gofrado/gofrado, 80µm/80µm.

CHARACTERISTICS:

Sandwich panel 20,5 mm thickness.
Aluminium: embossed/embossed, 80µm/80µm.

PRECIOS - PRICES

DIMENSIÓN PANEL - SIZE OF PANEL	4000x1200 mm
ESPESOR PANEL - THICKNESS OF PANEL	20,5 mm
ESPESOR ALUMINIO EXTERNO/INTERNO - THICKNESS OF EXTERNAL/INTERNAL ALUMINIUM	80/80 µm
ACABADO ALUMINIO - FINISH OF THE ALUMINIUM	gofrado-gofrado embossed-embossed
€ m ²	

Cantidad mínima: 48 m² - Minimum quantity: 48 m²

PHD30



CARACTERÍSTICAS:

Panel sandwich espesor 30,5 mm para exteriores. El espesor de 30,5 mm de la espuma y de 200µm del aluminio externo confieren resistencia ante los agentes atmosféricos y los choques, y junto al revestimiento interior de aluminio liso, hacen que este panel sea idóneo para la construcción de conductos exteriores para ambientes que requieren una elevada higiene.

CHARACTERISTICS:

PRECIOS - PRICES

DIMENSIÓN PANEL - SIZE OF PANEL	4000x1200 mm
ESPESOR PANEL - THICKNESS OF PANEL	30,5 mm
ESPESOR ALUMINIO EXTERNO/INTERNO - THICKNESS OF EXTERNAL/INTERNAL ALUMINIUM	200/80 µm
ACABADO ALUMINIO - FINISH OF THE ALUMINIUM	gofrado-liso embossed-smooth
€ m ²	

Cantidad mínima: 33,6 m² - Minimum quantity: 33,6 m²

Smooth outsider panel 30,5 mm thickness. The 30,5 mm foam and 200µm external aluminium, confer to the panel resistance to the atmospheric agents and accidental damage. This together with the smooth internal aluminium makes this panel ideal for the construction of outdoor ducts at the service of environments with high hygienic requirements.