

## PRECIOS - PRICES

| DIÁMETRO DE PASO AIRE<br>DIAMETER AIR PASSAGE | L<br>→ | ATENUACIÓN A 250 HZ<br>ATTENUATION AT 250 HZ |   |
|-----------------------------------------------|--------|----------------------------------------------|---|
| Ø mm                                          | mm     | dB(A)                                        | € |
| 80                                            | 500    | 9,5                                          |   |
| 100                                           | 500    | 8                                            |   |
| 125                                           | 500    | 6,5                                          |   |
| 140                                           | 500    | 5,5                                          |   |
| 150                                           | 500    | 5                                            |   |
| 160                                           | 500    | 5                                            |   |
| 180                                           | 500    | 4,5                                          |   |
| 200                                           | 500    | 4,5                                          |   |
| 224                                           | 500    | 4,5                                          |   |
| 250                                           | 500    | 4                                            |   |
| 280                                           | 500    | 3,5                                          |   |
| 300                                           | 500    | 3                                            |   |
| 315                                           | 500    | 3                                            |   |
| 355                                           | 500    | 3                                            |   |
| 400                                           | 500    | 2,5                                          |   |
| 80                                            | 1000   | 19                                           |   |
| 100                                           | 1000   | 16                                           |   |
| 125                                           | 1000   | 13                                           |   |
| 140                                           | 1000   | 11                                           |   |
| 150                                           | 1000   | 10                                           |   |
| 160                                           | 1000   | 10                                           |   |
| 180                                           | 1000   | 9                                            |   |
| 200                                           | 1000   | 9                                            |   |
| 224                                           | 1000   | 9                                            |   |
| 250                                           | 1000   | 8                                            |   |
| 280                                           | 1000   | 7                                            |   |
| 300                                           | 1000   | 6                                            |   |
| 315                                           | 1000   | 6                                            |   |
| 355                                           | 1000   | 6                                            |   |
| 400                                           | 1000   | 5                                            |   |
| 80                                            | 1500   | 28,5                                         |   |
| 100                                           | 1500   | 24                                           |   |
| 125                                           | 1500   | 19,5                                         |   |
| 140                                           | 1500   | 16,5                                         |   |
| 150                                           | 1500   | 15                                           |   |
| 160                                           | 1500   | 15                                           |   |
| 180                                           | 1500   | 13,5                                         |   |
| 200                                           | 1500   | 13,5                                         |   |
| 224                                           | 1500   | 13,5                                         |   |
| 250                                           | 1500   | 12                                           |   |
| 280                                           | 1500   | 10,5                                         |   |
| 300                                           | 1500   | 9                                            |   |
| 315                                           | 1500   | 9                                            |   |
| 355                                           | 1500   | 9                                            |   |
| 400                                           | 1500   | 7,5                                          |   |
| 80                                            | 2000   | 39                                           |   |
| 100                                           | 2000   | 32                                           |   |
| 125                                           | 2000   | 26                                           |   |
| 140                                           | 2000   | 22                                           |   |
| 150                                           | 2000   | 20                                           |   |
| 160                                           | 2000   | 20                                           |   |
| 180                                           | 2000   | 18                                           |   |
| 200                                           | 2000   | 18                                           |   |
| 224                                           | 2000   | 18                                           |   |
| 250                                           | 2000   | 16                                           |   |
| 280                                           | 2000   | 14                                           |   |
| 300                                           | 2000   | 12                                           |   |
| 315                                           | 2000   | 12                                           |   |
| 355                                           | 2000   | 12                                           |   |
| 400                                           | 2000   | 10                                           |   |

**CARACTERÍSTICAS:**

Silenciadores flexibles para conductos circulares, aislamiento 50 mm.

**ESTRUCTURA:**

Chapa exterior de aluminio con aislamiento acústico de lana mineral y chapa interna de aluminio. No inflamable conforme a DIN 4102 clase A1, resistente a 200 °C, radio de curvado de 3 veces el diámetro.

**FIJACIÓN:**

Empalme de encaje.

**CHARACTERISTICS:**

Flexible circular sound attenuators, insulation 50 mm.

**CONSTRUCTION:**

External sheet of aluminium with mineral wool insulation and inner sheet of aluminium. Not flammable in accordance with DIN 4102 class A1, resistant to 200 °C, bending radius equal to 3 diameters.

**FIXING:**

Coupling.

**DIBUJOS - DRAWINGS**