


PHD20



CARATTERISTICHE:

Pannello sandwich spessore 20,5 mm.

Alluminio: gofrato/gofrato, 80µm/80µm.

CHARACTERISTICS:

Sandwich panel 20,5 mm thickness.

Aluminium: embossed/embossed, 80µm/80µm.

PREZZI - PRICES

DIMENSIONE PANNELLO - SIZE OF PANEL	4000x1200 mm
SPESSORE PANNELLO - THICKNESS OF PANEL	20,5 mm
SPESSORE ALLUMINIO ESTERNO/INTERNO - THICKNESS OF EXTERNAL/INTERNAL ALUMINIUM	80/80 µm
FINITURA ALLUMINIO - FINISH OF THE ALUMINIUM	gofrato-gofrato embossed-embossed
€ m ²	

Quantità minima: 48 m² - Minimum quantity: 48 m²

PHD30



CARATTERISTICHE:

Pannello sandwich spessore 30,5 mm da esterno.

Lo spessore 30,5 mm della schiuma e 200µm dell'alluminio esterno, conferiscono resistenza agli agenti atmosferici e agli urti, nonché il rivestimento interno in alluminio liscio rendono il pannello idoneo per la costruzione di canali in esterno al servizio di ambienti ad elevata igiene.

PREZZI - PRICES

DIMENSIONE PANNELLO - SIZE OF PANEL	4000x1200 mm
SPESSORE PANNELLO - THICKNESS OF PANEL	30,5 mm
SPESSORE ALLUMINIO ESTERNO/INTERNO - THICKNESS OF EXTERNAL/INTERNAL ALUMINIUM	200/80 µm
FINITURA ALLUMINIO - FINISH OF THE ALUMINIUM	gofrato-liscio embossed-smooth
€ m ²	

Quantità minima: 33,6 m² - Minimum quantity: 33,6 m²

CHARACTERISTICS:

Smooth outsider panel 30,5 mm thickness. The 30,5 mm foam and 200µm external aluminium, confer to the panel resistance to the atmospheric agents and accidental damage. This together with the smooth internal aluminium makes this panel ideal for the construction of outdoor ducts at the service of environments with high hygienic requirements.