


PHD20



CARACTERISTICI:

Panou sandwich grosime 20,5 mm. Aluminu embosat/ embosat, 80µm/80µm.

CHARACTERISTICS:

Sandwich panel 20,5 mm thickness.
Aluminium: embossed/ embossed, 80µm/80µm.

PREȚURI - PRICES

DIMENSIUNE PANOU - SIZE OF PANEL	4000x1200 mm
GROSIME PANOU - THICKNESS OF PANEL	20,5 mm
GROSIME PANOU INTERN/EXTERN DIN ALUMINIU - THICKNESS OF EXTERNAL/INTERNAL ALUMINIUM	80/80 µm
FINISARE ALUMINIU - FINISH OF THE ALUMINIUM	embosat-embosat embossed-embossed
€ m ²	

Cantitate minimă: 48 m² - Minimum quantity: 48 m²

PHD30



CARACTERISTICI:

Panou lis la exterior grosime 30,5 mm. Grosimea de 30,5 mm a panoului și protecția de Aluminu de 200µm, conferă panoului rezistență la agenții atmosferici și deteriorări accidentale. Acestea, împreună cu aspectul lis al Aluminului conferă condiții ideale de folosire la exterior sau in construcții igienice.

PREȚURI - PRICES

DIMENSIUNE PANOU - SIZE OF PANEL	4000x1200 mm
GROSIME PANOU - THICKNESS OF PANEL	30,5 mm
GROSIME PANOU INTERN/EXTERN DIN ALUMINIU - THICKNESS OF EXTERNAL/INTERNAL ALUMINIUM	200/80 µm
FINISARE ALUMINIU - FINISH OF THE ALUMINIUM	embosat-embosat embossed-smooth
€ m ²	

CANTitate minimă: 33,6 m² - Minimum quantity: 33,6 m²

CHARACTERISTICS:

Smooth outsider panel 30,5 mm thickness. The 30,5 mm foam and 200µm external aluminium, confer to the panel resistance to the atmospheric agents and accidental damage. This together with the smooth internal aluminium makes this panel ideal for the construction of outdoor ducts at the service of environments with high hygienic requirements.