

## PREȚURI - PRICES

| DIAMETRU TRECERE AER<br>DIAMETER AIR PASSAGE | L<br>→ | ATENUARE LA 250 HZ<br>ATTENUATION AT 250 HZ |   |
|----------------------------------------------|--------|---------------------------------------------|---|
| Ø mm                                         | mm     | dB(A)                                       | € |
| 80                                           | 500    | 9,5                                         |   |
| 100                                          | 500    | 8                                           |   |
| 125                                          | 500    | 6,5                                         |   |
| 140                                          | 500    | 5,5                                         |   |
| 150                                          | 500    | 5                                           |   |
| 160                                          | 500    | 5                                           |   |
| 180                                          | 500    | 4,5                                         |   |
| 200                                          | 500    | 4,5                                         |   |
| 224                                          | 500    | 4,5                                         |   |
| 250                                          | 500    | 4                                           |   |
| 280                                          | 500    | 3,5                                         |   |
| 300                                          | 500    | 3                                           |   |
| 315                                          | 500    | 3                                           |   |
| 355                                          | 500    | 3                                           |   |
| 400                                          | 500    | 2,5                                         |   |
| 80                                           | 1000   | 19                                          |   |
| 100                                          | 1000   | 16                                          |   |
| 125                                          | 1000   | 13                                          |   |
| 140                                          | 1000   | 11                                          |   |
| 150                                          | 1000   | 10                                          |   |
| 160                                          | 1000   | 10                                          |   |
| 180                                          | 1000   | 9                                           |   |
| 200                                          | 1000   | 9                                           |   |
| 224                                          | 1000   | 9                                           |   |
| 250                                          | 1000   | 8                                           |   |
| 280                                          | 1000   | 7                                           |   |
| 300                                          | 1000   | 6                                           |   |
| 315                                          | 1000   | 6                                           |   |
| 355                                          | 1000   | 6                                           |   |
| 400                                          | 1000   | 5                                           |   |
| 80                                           | 1500   | 28,5                                        |   |
| 100                                          | 1500   | 24                                          |   |
| 125                                          | 1500   | 19,5                                        |   |
| 140                                          | 1500   | 16,5                                        |   |
| 150                                          | 1500   | 15                                          |   |
| 160                                          | 1500   | 15                                          |   |
| 180                                          | 1500   | 13,5                                        |   |
| 200                                          | 1500   | 13,5                                        |   |
| 224                                          | 1500   | 13,5                                        |   |
| 250                                          | 1500   | 12                                          |   |
| 280                                          | 1500   | 10,5                                        |   |
| 300                                          | 1500   | 9                                           |   |
| 315                                          | 1500   | 9                                           |   |
| 355                                          | 1500   | 9                                           |   |
| 400                                          | 1500   | 7,5                                         |   |
| 80                                           | 2000   | 39                                          |   |
| 100                                          | 2000   | 32                                          |   |
| 125                                          | 2000   | 26                                          |   |
| 140                                          | 2000   | 22                                          |   |
| 150                                          | 2000   | 20                                          |   |
| 160                                          | 2000   | 20                                          |   |
| 180                                          | 2000   | 18                                          |   |
| 200                                          | 2000   | 18                                          |   |
| 224                                          | 2000   | 18                                          |   |
| 250                                          | 2000   | 16                                          |   |
| 280                                          | 2000   | 14                                          |   |
| 300                                          | 2000   | 12                                          |   |
| 315                                          | 2000   | 12                                          |   |
| 355                                          | 2000   | 12                                          |   |
| 400                                          | 2000   | 10                                          |   |

**CARACTERISTICI:**

Atenuator flexibil circular de zgomot, cu izolație 50 mm.

**CONSTRUCȚIE:**

Folie externă de Aluminu cu izolație din vată minerală. Incombustibil conform standard DIN 4102 clasa A1, rezistent la 200°C, rază de curbă peste 3 diametre.

**MONTAJ:**

Racordare.

**CHARACTERISTICS:**

Flexible circular sound attenuators, insulation 50 mm.

**CONSTRUCTION:**

External sheet of aluminium with mineral wool insulation and inner sheet of aluminium. Not flammable in accordance with DIN 4102 class A1, resistant to 200 ° C, bending radius equal to 3 diameters.

**FIXING:**

Coupling.

**DESENE - DRAWINGS**