

PREȚURI - PRICES


■ STOC

	
	DUC
mm	€
125	
160	
200	
250	
315	
350	
400	
450	

DIMENSIUNI - MEASURES

Ø	A	B	C	D	E	F	G
125	135	60	123	45	170	22	67
160	175	76	158	57	200	23	80
200	215	96	199	88	265	27	115
250	270	127	248	112	309	30	142
315	335	180	313	138	378	30	168
350	370	195	348	205	430	33	238
400	420	220	398	171	466	36	207
450	470	276	448	233	520	41	274

DESENE - DRAWINGS



TABEL SELECȚIE - SELECTION TABLE

Model Model	A _k [m²]	Q [m³/h]		L _{wa} [dB(A)]		X _(0,25)		Dp _t [Pa]	
		min	max	min	max	min	max	min	max
DUC 125	0,01227	40	100	<20	27	6	12	10	50
DUC 160	0,02011	80	170	<20	28	7,4	16,2	10	50
DUC 200	0,03142	130	280	<20	29	10,4	17,1	10	50
DUC 250	0,04909	210	470	<20	32	12,3	26,4	10	50
DUC 315	0,07793	350	790	<20	32	15,1	35,1	10	50
DUC 350	0,09621	450	1000	<20	32	18,3	37,4	10	50
DUC 400	0,12566	600	1350	<20	33	20,6	40,7	10	50
DUC 450	0,15904	790	1760	<20	35	22,8	45,2	10	50

DUC

DIF



CARACTERISTICI:

Duză de introducere aer, cu bătaie lungă a jetului de aer, cu unghi maxim de înclinare de 30°.

CONSTRUCȚIE:

Aliaj de Aluminiu vopsit alb RAL 9010, cu garnitură de etanșare între elementul sferic și rama exterioară.

UTILIZARE:

Pentru instalare în plafon sau perete, pentru introducere. Înălțime montaj: 2,4-11,5 m.

MONTAJ:

Fixare prin șuruburi ascunse, o dată ce se îndepărtează inelul frontal.

CHARACTERISTICS:

Jet diffusers for long throw with orientable nozzle for a maximum angle of 30°.

CONSTRUCTION:

Aluminium alloy painted white RAL 9010 on the front with special gasket seal between the spherical element and the outer frame.

UTILIZATION:

For ceiling or wall installation for air delivery
Installation height:
2,4-11,5 m.

FIXING:

Fixing by means of hidden screws on the front once removed the visible part.

